

Technical Specification Fiber Optic Splice Closure

HTTC-07

Customer Approval			
	Name	Signature	Date
Approved by			

Contents

1. General	2
1.1 Description	2
1.2 Standards Comply	2
1.3 Applications Environment	2
2. Characteristics	3
3. Specifications	3
4. Product Picture	4
5. Configuration	4
5.1 Standard Accessories	4
5.2 Optional Accessories	5
6. Package	5

1. General

1.1 Description

Fiber optic splice closure is mainly applicable to the straight-through and branching of aerial cables, buried cables and duct cables, as well as the protection on cable joints.

Production type	Classification
HTTC-07	Fiber optic splice closure



Appearance of HTTC-07

1.2 Standards Comply

ITU L.13	Performance requirements for passive optical nodes: Sealed closures for outdoor environments
----------	--

1.3 Applications Environment

Item	Value
Operation temperature	-40 °C ~ +65 °C
Installation temperature	-15 °C ~ +40 °C
Storage temperature	-45 °C ~ +75 °C

2. Characteristics

Installation and reentry with a minimum of tools

Easy to be opened or closed

Re-enterable and reusable

All hardware are captivated

Capable for loading 1:2, 1:4, 1:8 PLC splitter

Tap Input, Tap Through (Output) and Drops connected are included

Closure can be flash tested

RoHS compliance

3. Specifications






Item	Specifications	Note
Material of housing	High-strength PP+GF	
Material of internal components	High-strength ABS	
Material of metal accessory	High-quality stainless steel	
External dimension(mm)	235mm x 185mm x 95mm	
Color	Black	
Number of ports	2	
Cable ports/Max.diameter of cable(mm)	2 main cable ports: 2 ports for cable max diameter 12mm. 8 drop cable ports with SC connector.	
Sealing type	Mechanical	
IP grade	IP65	
Splicing capacity(Max)	12	Optional as request

4.Product Picture





HTTC-07 product picture

5. Configuration**5.1 Standard Accessories**

No.	Name	Reference picture	Quantity	Remark
1	Heat-shrinkable protection sleeve		1 bag	L=45mm
2	Nylon cable tie		4 pcs	L=120mm
3	Installation tape		1 roll	black
4	Installation manual		1pc	English
5	Protective cover		8 pcs	

5.2 Optional Accessories

No.	Name	Model	Reference picture	Quantity	Remark
1	Pole-mounting kit	BZ11		1 set	
2	Wall-mounting kit			1 set	

6. Package

Standard

Double corrugated carton,50*45*44.5 CM, 16 in carton, about 15Kg