

# Technical Specification

## Fiber Optic Cable Distribution Box

### HTTPB-X22

Customer Approval			
	Name	Signature	Date
Approved by			

# Contents

1. General	2
1.1 Description	2
1.2 Standards Comply	2
1.3 Applications Environment	2
2. Characteristics	3
3. Specifications	3
3.1 Mechanical specifications	3
3.2 Optical specifications	4
4. Configuration	4
4.1 Optical splice trays	4
4.2 Accessory section	5
4.3 Optional Accessories	5
5. Product Picture	6
6. Package	6

**1. General**

**1.1 Description**

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

Production type	Classification
HTTB-X22	Fiber optic cable distribution box



Appearance of HTTB-X22

**1.2 Standards Comply**

The product is designed, manufactured and tested according to the standards as follows:

ITU-T L.13	Performance requirements for passive optical nodes: Sealed closures for outdoor environments
------------	--

**1.3 Applications Environment**

Item	Value
Operation temperature	-40 °C ~ +65 °C
Installation temperature	-15 °C ~ +40 °C
Storage temperature	-45 °C ~ +75 °C

## 2. Characteristics

Can accommodate 1x8 & 1X16 PLC splitter.

UV and weather proof.

Up to 16 FTTH drops.

Wall and pole mountable.


3 inlet ports( for cables with max diameter 12mm), 16 outlet ports.

ROHS compliance

## 3. Specifications

### 3.1 Mechanical specifications

Item	Specifications	Note
Material of housing	High-strength PC+ABS	
Material of internal components	High-strength ABS	
Material of metal accessory	High-quality stainless steel	
External dimension(mm)	310*260*105	
Color	Gray, black, white	
Number of distribution cable ports	3	
Number of drop cable ports	16	
3 Main Cable Ports	for cables max diameter 12mm	
Fiber cable dimension of drop port(mm)	2*3MM	
Capacity(Max)	16 Splices	
Max quantity splitter	1x8, 1x16 PLC splitter	
simplex adaptors	16	




### 3.2 Optical specifications

Item	Test Method	Specification	Note
Insertion loss(dB)	IEC61300-3-4-Method B	Mean $\leq$ 0.1dB · Maximum $\leq$ 0.3dB	
Return loss(dB)	IEC61300-3-6-Method 1	APC $\geq$ 60dB · UPC $\geq$ 50dB	



Random connection	IEC61300-3-4	Mean $\leq$ 0.15dB · Maximum $\leq$ 0.3dB	
Splitter		Refer to insert type splitter technical specification	
Repeatability	IEC 61300-2-2 500 cycles	During the test the difference between the initial measurement and each of the measurements after one cycle must be less than 0.20 dB, and should be cleaned otherwise, with a limit of 25 cleanings	




#### 4. Configuration

##### 4.1 Optical splice trays



No	Model	Pic	Capacity	Note
1	T033A		16F(2 layer)+1 PLC splitters	

##### 4.2 Accessory section

No.	Name	Reference picture	Quantity	Remark
1	Heat-shrinkable protection sleeve		1 bag	L=60mm
2	Nylon cable tie		12 pcs	L=120mm
3	Buffer tube for bunchy fiber		2 pcs	L=50 cm

4	Installation tape		1 roll	
5	Cable guard coil		3 pcs	
6	Installation manual		1pc	English

4.3 Optional Accessories

No.	Name	Model	Reference picture	Quantity	Remark
1	Pole-mounting kit	BZ13		1 set	
2	Wall-mounting kit			1 set	

5.Product Picture



HTTB-X22 product picture

6. Package

Standard

Double corrugated carton, 530\*335\*610 mm, 10 in carton, about 20 Kg.