

# Technical Specification Fiber Optic Splice Closure

## HTSC-F02

Customer Approval			
	Name	Signature	Date
Approved by			

# Contents

1. General	2
1.1 Description	2
1.2 Standards Comply	2
1.3 Applications Environment	2
2. Characteristics	3
3. Specifications	3
4. Product Picture	4
5. Configuration	4
5.1 Standard Accessories	4
5.2 Optional Accessories	5
6. Package	5

**1. General**

1.1 Description

Fiber optic splice closure is mainly applicable to the straight-through and branching of aerial cables, buried cables and duct cables, as well as the protection on cable joints.

Production type	Classification
HTSC-F02	Fiber optic splice closure



Appearance of HTSC-F02

1.2 Standards Comply

The product is designed, manufactured and tested according to the standards as follows:

ITU-T L.13	Performance requirements for passive optical nodes: Sealed closures for outdoor environments
------------	--

1.3 Applications Environment

Item	Value
Operation temperature	-40 °C ~ +65 °C
Installation temperature	-15 °C ~ +40 °C
Storage temperature	-45 °C ~ +75 °C

## 2. Characteristics

Compact design for FTTH application.  
 Central strength member fasten system included.  
 Construction and lightweight plastic provides strength and resistance to chemical and U.V attack  
 Installation and reentry with a minimum of tools  
 All hardware are included  
 RoHS compliance

## 3. Specifications

Item	Specifications	Note
Material of housing	High-strength PP+GF	
Material of internal components	High-strength ABS	
Material of metal accessory	High-quality stainless steel	
External dimension(mm)	179mm x 72mm x 26mm	
Color	Black	
Number of ports	2	
Cable ports/Max.diameter of cable(mm)	2 ports, each port for max diameter 6mm	
Sealing type	Mechanical	
Splicing capacity(Max)	4	Optional as request




## 4. Product Picture




HTSC-F02 product picture

**5. Configuration**

## 5.1 Standard Accessories

No.	Name	Reference picture	Quantity	Remark
1	Heat-shrinkable protection sleeve		1 bag	L=45mm
2	Nylon cable tie		4 pcs	L=120mm
3	Installation manual		1pc	English

## 5.2 Optional Accessories

No.	Name	Model	Reference picture	Quantity	Remark
1	Wall-mounting kit			1 set	

**6. Package**

Standard                      Double corrugated carton, 47\*43\*40 CM, 100 in carton, about 19Kg