

# Technical Specification Fiber Optic Splice Closure

## HTSC-FD22

Customer Approval			
	Name	Signature	Date
Approved by			

---

# Contents

1. General	2
1.1 Description	2
1.2 Standards Comply	2
1.3 Applications Environment	2
2. Characteristics	3
3. Specifications	3
4. Product Picture	4
5. Configuration	4
5.1 Standard Accessories	4
5.2 Optional Accessories	5
6. Package	5

**1. General**

1.1 Description

Fiber optic splice closure is mainly applicable to the straight-through and branching of aerial cables, buried cables and duct cables, as well as the protection on cable joints.

Production type	Classification
HTSC-FD22	Fiber optic splice closure



Appearance of HTSC-FD22

1.2 Standards Comply

The product is designed, manufactured and tested according to the standards as follows:

ITU-T L.13	Performance requirements for passive optical nodes: Sealed closures for outdoor environments
------------	--

1.3 Applications Environment

Item	Value
Operation temperature	-40 °C ~ +65 °C
Installation temperature	-15 °C ~ +40 °C
Storage temperature	-45 °C ~ +75 °C

## 2. Characteristics

Compact design for FTTH application.

Hinged structure

Sheath retention & central strength member fasten system included.

Ribbed closure construction-lightweight plastic offers strength and resistance to chemical and U.V attack

Installation and reentry with a minimum of tools


All hardware are included

RoHS compliance

## 3. Specifications

Item	Specifications	Note
Material of housing	High-strength PP+GF	
Material of internal components	High-strength ABS	
Material of metal accessory	High-quality stainless steel	
External dimension(mm)	201mm x 76mm x34mm	
Color	Black	
Number of ports	4	
Cable ports/Max.diameter of cable(mm)	4 ports: 2 ports for cable with max.18mm, 2 ports for cable with max.11mm.	
Sealing type	Mechanical	
Splicing capacity(Max)	0	Optional as request




## 4.Product Picture




HTSC-FD22 product picture

## 5. Configuration

### 5.1 Standard Accessories

No.	Name	Reference picture	Quantity	Remark
1	Nylon cable tie		6 pcs	L=120mm
2	Installation manual		1pc	English
3	Sponge article		1pc	

### 5.2 Optional Accessories

No.	Name	Model	Reference picture	Quantity	Remark
1	Wall-mounting kit			1 set	

## 6. Package

Standard Double corrugated carton, 66\*43.5\*37.5 CM, 80 in carton, about 18.5 Kg.