

Technical Specification
Fiber Optic Splice Closure
HTSC-150A

Customer Approval			
	Name	Signature	Date
Approved by			

Contents


1. General	2
1.1 Description	2
1.2 Standards Comply	2
1.3 Applications Environment	2
2. Characteristics	3
3. Specifications	3
3.1 Mechanical specifications	3
3.2 Optical specifications	4
4. Configuration	4
4.1 Optical splice trays	4
4.2 Accessory section	4
4.3 Optional Accessories	5
5. Product Picture	6
6. Package	6

1. General

1.1 Description

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

Production type	Classification
HTSC-150A	Fiber optic cable distribution box



Appearance of HTSC-150A

1.2 Standards Comply

The product is designed, manufactured and tested according to the standards as follows:

ITU-T L.13	Performance requirements for passive optical nodes: Sealed closures for outdoor environments
------------	--

1.3 Applications Environment

Item	Value
Operation temperature	-40 °C ~ +65 °C
Installation temperature	-15 °C ~ +40 °C
Storage temperature	-45 °C ~ +75 °C

2. Characteristics

May be used for cut, uncut and taut sheath applications.

May be used for all fiber optic cable.

Sheath retention & central strength member fasten system included.

Ribbed closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack

Installation and reentry with a minimum of tools

Re-enterable and reusable

All hardware are included

RoHS compliance

3. Specifications

3.1 Mechanical specifications


Item	Specifications	Note
Material of housing	High-strength PP+GF	
Material of internal components	High-strength ABS	
Material of metal accessory	High-quality stainless steel	
External dimension(mm)	352*200*101	
Color	Black	
Number of distribution cable ports	3	
Number of drop cable ports	16	
3 Main Cable Ports	for cables with max diameter 13mm	
Fiber cable dimension of drop port(mm)	2*3MM	
Capacity(Max)	24 Splices	
Max quantity splitter	LGX type PLC splitter	
simplex adaptors	16	

3.2 Optical specifications






Item	Test Method	Specification	Note
Insertion loss(dB)	IEC61300-3-4-Method B	Mean \leq 0.1dB · Maximum \leq 0.3dB	
Return loss(dB)	IEC61300-3-6-Method 1	APC \geq 60dB · UPC \geq 50dB	
Random connection	IEC61300-3-4	Mean \leq 0.15dB · Maximum \leq 0.3dB	
Splitter		Refer to insert type splitter technical specification	
Repeatability	IEC 61300-2-2 500 cycles	During the test the difference between the initial measurement and each of the measurements after one cycle must be less than 0.20 dB, and should be cleaned otherwise, with a limit of 25 cleanings	




4. Configuration

4.1 Optical splice trays



No	Model	Pic	Capacity	Note
1	T088A		24F(2 layer)	

4.2 Accessory section


No.	Name	Reference picture	Quantity	Remark
1	Heat-shrinkable protection sleeve	 	1 bag	L=45mm (T088A)
2	Nylon cable tie		12 pcs	L=120mm
3	Buffer tube for bunchy fiber		n pcs	Each piece: OD=4.5mm, L=50cm QTY: n=trays number
4	Installation tape		1 roll	
5	Hose hoops		3 pcs	

6	Sealing tape		1 rolls	Black
7	Special wrench		1set	
8	Installation manual		1pc	English

4.3 Optional Accessories

No.	Name	Model	Reference picture	Quantity	Remark
1	Pole-mounting kit	BZ09		1 set	
2	Wall-mounting kit			1 set	

5. Product Picture



HTSC-150A product picture

6. Package

Standard

Double corrugated carton, 680*375*580 mm, 10 in carton, about 16 Kg.